

## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
8 April 2004 (08.04.2004)

PCT

(10) International Publication Number  
**WO 2004/030133 A1**

(51) International Patent Classification<sup>7</sup>: **H01M 8/02, 8/24**

(21) International Application Number:  
PCT/NL2003/000663

(22) International Filing Date:  
29 September 2003 (29.09.2003)

(25) Filing Language: Dutch

(26) Publication Language: English

(30) Priority Data:  
1021547 27 September 2002 (27.09.2002) NL

(71) Applicant (for all designated States except US): **STICHT-  
ING ENERGIEONDERZOEK CENTRUM NEDER-  
LAND [NL/NL];** Westerduinweg 3, NL-1755 LE Petten  
(NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **RIETVELD, Gijs-  
bertus [NL/NL];** Bohemenstraat 8, NL-1827 EH Alkmaar  
(NL). **VAN DRUTEN, Gerry, Martina, Regina [NL/NL];**  
Avegaarstraat 4, NL-1825 LB Alkmaar (NL).

(74) Agent: **VAN WESTENBRUGGE, Andries;** Nederland-  
sch Octrooibureau, Scheveningseweg 82, P.O. Box 29720,  
NL-2502 LS The Hague (NL).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,  
CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE,  
GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR,  
KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK,  
MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT,  
RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR,  
TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,  
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,  
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,  
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

- with international search report
- before the expiration of the time limit for amending the  
claims and to be republished in the event of receipt of  
amendments

For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.

(54) Title: **ELECTRODE-SUPPORTED FUEL CELL**

(57) Abstract: Cathode-supported fuel cell wherein the cathode support comprises a porous part made of an alloy containing iron and chromium and more particularly stainless steel. The anode has a thickness of 1-50 µm and preferably consists of nickel/nickel oxide. The cathode preferably consists of LSM material. Such an electrode-supported fuel cell can be produced by providing a metallic support containing at least iron or chromium by means of sintering, preferably starting from a powder, successively applying thereto an electrode, electrolyte and other electrodes. With this method a cathode is applied to the metallic support and the combination obtained is sintered at a temperature between 1000 and 1200 °C.

WO 2004/030133 A1